

PRODUCT DATA SHEET

5100HD Gas Analyzers for Measuring O₂ in Process Gas

Based on tunable diode laser absorption spectroscopy (TDLAS), the 5100HD analyzes oxygen in a variety of gas streams.

The laser-based measurement system is free of interferences from other sample stream components, providing fast and accurate results. Maintenance requirements are minimal, as the gas stream being analyzed never makes contact with the key measurement components – the laser light source and detector.

For samples requiring conditioning or heat to maintain the sample stream in a measurable gas phase, the 5100HD can include pressure and flow regulators, a 150°C (302°F) heater and/or a pump or educator.

Non-contact measurement

The sample never contacts the key optical components, reducing maintenance requirements

Line lock

The wavelength of interest is constantly verified using an integrated reference

Designed for use in difficult environments

Can be installed in many environments, including those defined as hazardous



KEY BENEFITS

- Real-time performance monitoring
- Low maintenance cost and requirements
- Reduced downtime
- IP 65/Type 4X enclosure
- Fully-integrated sample handling

APPLICATIONS

- Process safety
- Headspace analysis

KEY MARKETS

- Chemicals
- Oil & gas
- Petrochemicals
- Refining

PERFORMANCE SPECIFICATIONS

Typical operating range	0-5% and 0-25%
Accuracy	±2000 ppm (v/v) or ±2% of reading, whichever is greater
Ambient temperature	-20 to +50°C (-4 to 122°F).
Relative humidity	0 to 90%, noncondensing
Sample flow rate	1 to 10 SLPM recommended (2-20 SCFH)
Sample cell pressure	70 to 170 kPa absolute (10-25 psia) For higher pressures, consult AMETEK
Speed of response	< 1 second photometric response. Total system response is dependent on sample flowrate
Outputs	Display and keypad. Fast ethernet (IEEE802.3) RS485 serial port, isolated (supports Modicon Modbus RTU) (1) isolated 4-20 mA loop-powered analog output (4) dry relay contacts. Contact rating 30 VAC, 60 VDC, 100 VA resistive
Electrical requirements	120 VAC (108-132V); 47-63 Hz, or 240 VAC (216-264V), 47-63 Hz 24 VDC (Consult AMETEK)
Power requirements	5100HD: 450W, 105W without heater
Physical rimensions (W x H x D)	5100HD: 830 x 674 x 305 mm (32.7 x 26.5 x 12.0 in.) 5100HD ATEX Zone 1: 1143 x 648 x 436 mm (45.0 x 25.5 x 17.1 in.)
Weight	5100HD: 60 Kg (132 lb)
Enclosure	IP-65, TYPE 4X
Approvals and certifications	Certified to meet multiple ATEX, IECEx, CSA and NEC standards for hazardous areas Consult AMETEK for more details

New England - ETA Process Instrumentation
119 Foster Street, Bldg #6
Peabody, MA 01960
Tel: (978) 532-1330
www.etapii.com
sales@etapii.com

Upstate NY - Martech Controls
2000 Teall Avenue
Syracuse, NY 13026
Tel: (315) 876-9120
www.martechcontrols.com
sales@martechcontrols.com



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0368 Rev 8 (0718)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



To find out more or request a quote visit our website

