

PRODUCT DATA SHEET

5100HD Gas Analyzer for the Measurement of Carbon Dioxide in Natural Gas

Carbon dioxide (CO₂) is one of the highest level impurities found in well head natural gas. It must be removed to meet pipe-line quality British thermal unit (BTU) standard specifications for consumer gas and to protect pipelines from corrosion which occurs when CO₂ and water (H₂O) combine to form carbonic acid.

The AMETEK 5100HD is an extractive-type CO₂ analyzer designed for hot/wet sample analysis. There is no sample conditioning for the analyzer system, just sample handling to transport the sample.

The 5100HD measures at a wavelength free of interferences from the hydrocarbons typically found in natural gas streams to provide continuous and accurate results. The 5100HD uses a sealed reference cell for continuous online optical system verification and offers high specificity, and sensitivity.

For customers looking to measure multiple components with one analyzer, the 5100HD can simultaneously measure water vapor and CO₂ measurements in natural gas streams.

Non contact measurement

The sample never contacts the key optical components, reducing maintenance.

Line lock

The wavelength of interest is constantly verified using an integrated reference.

Designed for use in difficult environments

Can be installed in many environments, including those defined as hazardous.



KEY BENEFITS

- Real-time performance monitoring
- Low maintenance cost and requirements
- Reduced downtime
- IP 65/Type 4X enclosure
- Fully-integrated sample handling

APPLICATIONS

- Tariff or custody transfer
- Natural gas sweetening

KEY MARKETS

- Natural gas
- Petrochemicals
- Refining

PERFORMANCE SPECIFICATIONS

Typical ranges & performance	Ranges: 0-50 ppm (min), 0-100% (max) Accuracy $\pm 2\%$ of reading
Ambient temperature	-20 to +50°C (-4 to 122°F)
Relative humidity	0 to 90%, non-condensing
Sample flow rate	1 to 10 SLPM recommended (2-20 SCFH)
Sample cell pressure	70 to 170 kPa absolute (10-25 psia)
Speed of response	<1 second photometric response Total system response is dependent on sample flowrate
Electrical requirements	120 VAC (108-132V); 47-63 Hz, or 240 VAC (216-264V), 47-63 Hz; 24 VDC (Consult AMETEK)
Power requirements	5100HD: 450W; 105W without heater
Outputs	Keypad and display Fast ethernet (IEEE802.3) RS485 serial port, isolated (supports Modicon Modbus RTU) (1) single isolated 4-20 mA loop-powered analog output (4) dry relay contacts. Contact rating 30 VAC, 60 VDC, 100 VA resistive
Physical dimensions (W x H x D)	5100HD 830 x 674 x 305 mm (32.7 x 26.5 x 12.0 in.)
Weight	5100HD CEC/NEC Class I Division 2: 60 Kg (132 lb)
Enclosure	IP65 and Type 4X
Approvals and certifications	Certified to meet multiple ATEX, IECEx, CSA, NEC and Inmetro standards for hazardous areas Consult AMETEK for more details

New England - ETA Process Instrumentation
119 Foster Street, Bldg #6
Peabody, MA 01960
Tel: (978) 532-1330
www.etapii.com
sales@etapii.com

Upstate NY - Martech Controls
2000 Teall Avenue
Syracuse, NY 13026
Tel: (315) 876-9120
www.martechcontrols.com
sales@martechcontrols.com



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0220 Rev 10 (0818)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

