

PRODUCT DATA SHEET

5100P TDLAS Moisture Analyzer

Lightweight and rugged portable moisture (water vapor) analyzer delivering reliable, accurate measurements in natural gas

The 5100P analyzer provides simple, easy-to-use moisture analysis using tunable diode laser absorption spectroscopy (TDLAS) in a durable, lightweight, and portable package for measurements in natural gas. Designed to be intuitive to start-up and log data, the 5100P is the tool-of-choice for users needing to perform measurements in remote locations or verify fixed analyzer installations.

Minimal maintenance required

The non-contact TDLAS sensing technology means that both the laser source and the detector are kept separate from the process. This eliminates the need for routine calibration, cleaning of the sensor or interferences from process contaminants, increasing measurement uptime and reducing total cost of ownership.

To reduce the possibility of over pressuring the cell, or introducing contaminants, an integrated sample conditioning panel is included with the 5100P analyzer.

Measurement confidence

To ensure accurate measurement, every 5100P is factory calibrated and tested prior to shipment. The 5100P also uses an internal reference to prevent any wavelength shift, when operated in the field. Although the 5100P, with its high-sensitivity, moisture-specific measurement will not be impacted by other constituents in the natural gas, the laser-source output must be monitored and controlled continuously to deliver an accurate moisture measurement every time.

Increased efficiency

With an integrated sample system, using the 5100P is simple and easy. A measurement can be made in minutes, just connect the sample tubing, power up the analyzer, and start flow through the system. The TDLAS technology in the 5100P delivers immediate response to changes in the moisture content of the natural gas. Users no longer have to wait hours for the sensor to equilibrate and can make more measurements in less time. The 5100P is certified for use in hazardous areas so there are no costly enclosures or hot work permits needed to operate the analyzer.



KEY BENEFITS

- Fast response, highly accurate measurements using TDLAS technology
- Certified for use in hazardous areas
- Integrated sample system removes contaminants
- Rechargeable battery for at least eight hours of operation
- Lightweight package simplifies transporting the device between locations

APPLICATIONS

- Monitoring H₂O in natural gas pipelines, processing and fuel lines

KEY MARKETS

NATURAL GAS

- Transmission pipelines
- Custody transfer
- Dehydration
- Underground storage
- Gas processing
- Gas compressor and metering stations

PERFORMANCE SPECIFICATIONS

Technology	Tunable diode laser absorption spectroscopy
Speed of response	<1 second photometer response; <15 seconds to T90 at 2 SLPM of sample gas
Range	0 – 2500 ppmv
Accuracy	2% of reading or +/- 4 ppmv (whichever is greater)
Repeatability	2% of reading or +/- 4 ppmv (whichever is greater)
Limit of detection	5 ppmv in methane
User interface	On board display and USB
Battery type	Rechargeable sealed lead acid battery
Sample cell pressure	Atmospheric
Ambient temperature	-20 to +50°C (-4 to +122°F)
Sample temperature	-20 to +50°C (-4 to +122°F)
Inlet pressure range for sample panel	1.03 to 17.2 barg (15 to 250 psig)
Recommended sample flow rate	1 to 2 SLPM (2 to 4 SCFH)
Physical dimensions	25.1 cm x 20.9 cm x 40.1 cm (9.9 in x 8.2 in x 15.8 in); approximately 13.2 kg (29.1 lbs)
Sample wetted parts	304 Stainless steel, 316 stainless steel, SiO2 glass, EPDM
Power requirements	110-240 VAC 50-60 Hz for battery charging and instrument use when battery is depleted
Environmental rating	Pollution degree: 2 Overvoltage category: I Maximum altitude: 2000 meters Ingress rating: IP 65
Pending certifications	ATEX/IEC Ex II 3G na IC Op is IICT3 Gc -20°C < Tamb < +50°C NEC Class 1, Div 2, GRP A, B, C, D, T3 -20°C to +50°C

New England - ETA Process Instrumentation
119 Foster Street, Bldg #6
Peabody, MA 01960
Tel: (978) 532-1330
www.etapii.com
sales@etapii.com

Upstate NY - Martech Controls
2000 Teall Avenue
Syracuse, NY 13026
Tel: (315) 876-9120
www.martechcontrols.com
sales@martechcontrols.com



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0544 Rev 1 (0119)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

