

PRODUCT DATA SHEET

ta7000 UHP Gas Purity Monitors

Designed for today's ultra-high-purity (UHP) applications

The ta7000 platform includes a dedicated sample processing system, a single high-sensitivity detector and on-board data analysis electronics. Two distinct models are available and each is equipped to detect a wide range of common gas impurities:

ta7000R - Hydrogen (H₂) and carbon monoxide (CO) reduction gas detector (RGD):

- Detection limit below 500 parts per trillion (ppt)

ta7000F - Carbon dioxide (CO₂), methane (CH₄) and non-methane hydrocarbons flame ionization detector (FID):

- Detection limit below 500 ppt

Over time, gas distribution systems are susceptible to upsets due to expiration of flow components, component outgassing, and accidental purifier overload. It is crucial to detect contamination before it spreads through the vast network of gas piping runs. Continuous monitoring of UHP gas identifies an upset before it becomes a crisis. ta7000 monitors will selectively and automatically measure these impurities in UHP bulk gases.

Quality control tool

A ta7000 system provides assurance that your house gases comply with specifications where it matters most – at the source of the UHP gas distribution system. By monitoring this point of reference, you can continuously validate and defend the quality of purified gas at this critical juncture.

Advanced detection technology

The EDL integration mode is one of the many enhancements that give the ta7000 analyzers their unparalleled sensitivity during continuous operation. EDL employs an advanced algorithm to isolate measurement signals while filtering out random electronic noise. This results in an accurate and highly precise profile of the quality of your bulk gas.



KEY BENEFITS

- High sensitivity
- Broad detection range
- Cost-efficient maintenance and operation
- Best value and performance
- On-board gas regulation
- Carrier gas purifier
- Rotorless valves
- Proven chromatograph
- Internal calibration system
- Preconfigured for use on specific types of gas



APPLICATIONS

- Purifier outlet monitoring
- Air separation
- Gas purity monitoring



KEY MARKETS

- Semiconductor manufacturing
- LCD/OLED display manufacturing

To find out more or request a quote visit our website

ametekpi.com

PERFORMANCE SPECIFICATIONS

ta7000R Specifications:

Sample gas	Model	H ₂ parts per billion (ppb)	CO ppb
Nitrogen (N ₂)	ta7000R-N ₂	< 0.5	< 0.5
Argon (Ar)	ta7000R-Ar	< 0.5	< 0.5
Helium (He)	ta7000-He	< 0.5	< 0.5
Oxygen (O ₂)	ta7000-O ₂	< 0.5	< 0.5
Carbon dioxide (CO ₂)	ta7000-CO ₂	< 0.5	< 0.5
Performance specifications			
Accuracy, EDL mode		Greater of ±0.25 ppb H ₂ ; ±0.25 ppb CO; ±10% of reading	
Range		0 to 199.9 ppb	
Response time		Five minutes to 99% response; 30 minutes to 75% response in EDL mode Response time is independent of sample concentration	
Ambient operating temperature		16 to 32°C (60 to 90°F)	
Sample compatibility		Specific models available for N ₂ , Ar, He, or O ₂ analysis	
Resolution/display		0.1 ppb	
Resolution/communication ports		0.01 ppb	
Sample gas supplies			
Inlet pressure range		70 to 90 psig (4.8 to 6.2 bar)	
Inlet pressure stability		±2%, regulator required	
Return pressure		Atmospheric vent is optimal; ±0.5 psig max	
Flow rate		300 sccm minimum; sample bypass at 50 sccm	
Temperature		16 to 38°C (60 to 100°F), optimum when temperature maintained ±2°C	
Maximum impurity levels		200 ppb moisture, CO ₂ , hydrocarbons	
Chassis			
Dimensions (W x H x D)		430 x 180 x 670 mm (16.8 x 7 x 26.5 in.)	
Weight		15.9 kg (35 lb.)	
Power		100-120 VAC, 50/60 Hz; 200-240 VAC, 50/60 Hz	
Gas ports			
Carrier/sample inlet		1/4-inch face seal fitting	
Actuator air		1/8-inch VICI compression	
Sample outlet		1/16-inch VICI compression	
Aux (calibration)		1/16-inch VICI compression	
Outputs			
Display		LCD graphics, backlit, 100mm x 150mm	
Printer port		Concentration, chromatogram, and diagnostic reports	
Serial PLC port		Concentration data and alarms via RS-232	
4-20mA (optional)		Concentration signals and status relay contacts	

New England - ETA Process Instrumentation

119 Foster Street, Bldg #6
Peabody, MA 01960
Tel: (978) 532-1330
www.etapii.com
sales@etapii.com

Upstate NY - Martech Controls

2000 Teall Avenue
Syracuse, NY 13026
Tel: (315) 876-9120
www.martechcontrols.com
sales@martechcontrols.com



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0192 Rev 6 (0918)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



To find out more or request a quote visit our website



PERFORMANCE SPECIFICATIONS

ta7000F Specifications:

Sample gas	Model	CH ₄ ppb	CO ₂ ppb	NMHC ppb
N ₂	ta7000F-N ₂	< 0.5	< 1.0	< 2.0
Ar	ta7000F-Ar	< 0.5	< 1.0	< 2.0
He	ta7000F-He	< 0.5	< 1.0	< 2.0
O ₂	ta7000F-O ₂	< 0.1	< 2.0	< 2.0
Hydrogen (H ₂)	ta7000F-H ₂	< 0.1	< 1.0	< 2.0
CO ₂	ta7000F-CO ₂	< 0.1		< 2.0
Performance				
Accuracy, EDL mode		Greater of ±0.25 ppb CH ₄ ; ±0.5 ppb CO ₂ ; ±1.0 ppb NMHC; ±10% of reading; ±1.0 ppb CO		
Range		0 to 199.9 ppb		
Response time		10 minutes to 99% response. 60 minutes to 75% response in EDL mode Response time is independent of sample concentration		
Ambient operating temperature		16 to 32°C (60 to 90°F)		
Sample compatibility		Specific models available for N ₂ , Ar, He, O ₂ , or H ₂ analysis		
Resolution/display		0.1 ppb		
Resolution/communication ports		0.01 ppb		
Sample gas supplies				
Inlet pressure range		70 to 90 psig (4.8 to 6.1 bar)		
Inlet pressure stability		±2%, regulator required		
Return pressure		Atmospheric vent is optimal, ±0.5 psig maximum		
Flow rate		300 sccm minimum, sample at 50 sccm		
Temperature		16 to 38°C (60 to 100°F), optimum when temperature maintained +2°C		
Maximum impurity levels		200 ppb moisture, CO ₂ , hydrocarbons		
Chassis				
Dimensions (W x H x D)		430 x 180 x 70 mm (16.8 x 7 x 26.5 in.)		
Weight		15.9 kg (35 lb.)		
Power		100-120 VAC, 50/60 Hz; 200-240 VAC, 50/60 Hz		
Gas ports				
Carrier/sample inlet		1/4-inch face seal fitting		
Sample inlet		1/4-inch face seal fitting (H ₂ and O ₂ models only)		
FID air		1/16-inch VICI compression		
FID H ₂		1/16-inch VICI compression		
Aux (calibration)		1/16-inch VICI compression		
Sample outlet		1/16-inch VICI compression		
FID H ₂ shut-off		1/8-inch VICI compression – supplied at 57 psi (3.9 bar)		
Actuator gas		1/8-inch VICI compression		
Outputs				
Display		LCD graphics, backlit, 100mm x 150mm		
Printer port		Concentration, chromatogram, and diagnostic reports		
Serial PLC port		Concentration data and alarms via RS-232		
4-20mA (optional)		Concentration signals and status relay contacts		

SALES, SERVICE & MANUFACTURING

USA - Pennsylvania

150 Freeport Road
Pittsburgh PA 15238
Tel: +1 412 828 9040
Fax: +1 412 826 0399

USA - Delaware

455 Corporate Blvd.
Newark DE 19702
Tel: +1 302 456 4400
Fax: +1 302 456 4444

Canada - Alberta

2876 Sunridge Way NE
Calgary AB T1Y 7H9
Tel: +1 403 235 8400
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

USA

Tel: +1 713 466 4900
Fax: +1 713 849 1924

Brazil

Tel: +55 19 2107 4100

France

Tel: +33 1 30 68 89 20
Fax: +33 1 30 68 89 99

Germany

Tel: +49 2159 9136 0
Fax: +49 2159 9136 39

India

Tel: +91 80 6782 3200
Fax: +91 80 6780 3232

Singapore

Tel: +65 6484 2388
Fax: +65 6481 6588

China

Beijing
Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
Chengdu
Tel: +86 28 8675 8111
Fax: +86 28 8675 8141
Shanghai
Tel: +86 21 5868 5111
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0192 Rev 6 (0918)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



To find out more or request a quote visit our website

